

EPC2055 – Enhancement Mode Power Transistor

 V_{DS} , 40 V $R_{DS(on)}$, 3.6 m Ω I_D , 29 A

Gallium Nitride's exceptionally high electron mobility and low temperature coefficient allows very low $R_{DS(on)}$, while its lateral device structure and majority carrier diode provide exceptionally low Q_G and zero Q_{RR} . The end result is a device that can handle tasks where very high switching frequency, and low on-time are beneficial as well as those where on-state losses dominate.

Maximum Ratings

PARAMETER		VALUE	UNIT
V_{DS}	Drain-to-Source Voltage (Continuous)	40	V
	Drain-to-Source Voltage (up to 10,000 5 ms pulses at 150 °C)	48	
I_D	Continuous ($T_A = 25^\circ\text{C}$)	29	A
	Pulsed (25°C , $T_{PULSE} = 300 \mu\text{s}$)	161	
V_{GS}	Gate-to-Source Voltage	6	V
	Gate-to-Source Voltage	-4	
T_J	Operating Temperature	-40 to 150	°C
T_{STG}	Storage Temperature	-40 to 150	

Thermal Characteristics


PARAMETER		TYP	UNIT
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	1	°C/W
$R_{\theta JB}$	Thermal Resistance, Junction-to-Board	2.5	
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient (Note 1)	64	

Note 1: $R_{\theta JA}$ is determined with the device mounted on one square inch of copper pad, single layer 2 oz copper on FR4 board. See https://epc-co.com/epc/documents/product-training/Appnote_Thermal_Performance_of_eGaN_FETs.pdf for details.

Static Characteristics ($T_J = 25^\circ\text{C}$ unless otherwise stated)

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
BV_{DSS}	Drain-to-Source Voltage	$V_{GS} = 0 \text{ V}$, $I_D = 0.5 \text{ mA}$	40			V
I_{DSS}	Drain-Source Leakage	$V_{GS} = 0 \text{ V}$, $V_{DS} = 32 \text{ V}$		0.01	0.4	mA
I_{GSS}	Gate-to-Source Forward Leakage	$V_{GS} = 5 \text{ V}$		0.01	0.8	
	Gate-to-Source Forward Leakage [#]	$V_{GS} = 5 \text{ V}$, $T_J = 125^\circ\text{C}$		0.1	5	
	Gate-to-Source Reverse Leakage	$V_{GS} = -4 \text{ V}$		0.01	0.4	
$V_{GS(TH)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}$, $I_D = 7 \text{ mA}$	0.7	1.1	2.5	V
$R_{DS(on)}$	Drain-Source On Resistance	$V_{GS} = 5 \text{ V}$, $I_D = 15 \text{ A}$		3	3.6	m Ω
V_{SD}	Source-Drain Forward Voltage	$I_S = 0.5 \text{ A}$, $V_{GS} = 0 \text{ V}$		1.9		V

[#] Defined by design. Not subject to production test.



EPC2055 eGaN® FETs are supplied only in passivated die form with solder bars.
Die Size: 2.5 mm x 1.5 mm

Applications

- DC-DC Converters
- Isolated DC-DC Converters
- Sync rectification
- High frequency (2 MHz) Ultra-thin Point of Load Converters with Input 12 V – 24 V
- Lidar
- USB-C Battery Chargers
- LED Lighting
- 12 V – 24 V Input Motor Drivers

Benefits

- Ultra High Efficiency
- No Reverse Recovery
- Ultra Low Q_G
- Small Footprint



Dynamic Characteristics ($T_j = 25^\circ\text{C}$ unless otherwise stated)

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
C_{ISS}	Input Capacitance [#]	$V_{DS} = 20\text{ V}, V_{GS} = 0\text{ V}$		841	1111	pF
C_{RSS}	Reverse Transfer Capacitance			8.8		
C_{OSS}	Output Capacitance [#]			408	612	
$C_{OSS(ER)}$	Effective Output Capacitance, Energy Related (Note 2)	$V_{DS} = 0\text{ to }20\text{ V}, V_{GS} = 0\text{ V}$		574		
$C_{OSS(TR)}$	Effective Output Capacitance, Time Related (Note 3)			668		
R_G	Gate Resistance			0.4		Ω
Q_G	Total Gate Charge [#]	$V_{DS} = 20\text{ V}, V_{GS} = 5\text{ V}, I_D = 15\text{ A}$		6.6	8.5	nC
Q_{GS}	Gate-to-Source Charge	$V_{DS} = 20\text{ V}, I_D = 15\text{ A}$		2.3		
Q_{GD}	Gate-to-Drain Charge			0.7		
$Q_{G(TH)}$	Gate Charge at Threshold			1.6		
Q_{OSS}	Output Charge [#]	$V_{DS} = 20\text{ V}, V_{GS} = 0\text{ V}$		13	20	
Q_{RR}	Source-Drain Recovery Charge			0		

Defined by design. Not subject to production test.

Note 2: $C_{OSS(ER)}$ is a fixed capacitance that gives the same stored energy as C_{OSS} while V_{DS} is rising from 0 to 50% BV_{DSS} .

Note 3: $C_{OSS(TR)}$ is a fixed capacitance that gives the same charging time as C_{OSS} while V_{DS} is rising from 0 to 50% BV_{DSS} .

Figure 1: Typical Output Characteristics at 25°C




Figure 2: Transfer Characteristics




Figure 3: $R_{DS(on)}$ vs. V_{GS} for Various Drain Currents




Figure 4: $R_{DS(on)}$ vs. V_{GS} for Various Temperatures




Figure 5a: Capacitance (Linear Scale)




Figure 5b: Capacitance (Log Scale)




Figure 6: Output Charge and C_{OSS} Stored Energy




Figure 7: Gate Charge




Figure 8: Reverse Drain-Source Characteristics




Figure 9: Normalized On-State Resistance vs. Temperature




Figure 10: Normalized Threshold Voltage vs. Temperature




Figure 11: Safe Operating Area








Figure 12: Transient Thermal Response Curves



TAPE AND REEL CONFIGURATION

4 mm pitch, 8 mm wide tape on 7" reel



Loaded Tape Feed Direction →



Die orientation dot
Gate solder bar is under this corner


Die is placed into pocket solder bump side down (face side down)

EPC2204 (Note 1)	Dimension (mm)		
	Target	MIN	MAX
a	8.00	7.90	8.30
b	1.75	1.65	1.85
c (Note 2)	3.50	3.45	3.55
d	4.00	3.90	4.10
e	4.00	3.90	4.10
f (Note 2)	2.00	1.95	2.05
g	1.50	1.50	1.60
h	0.50	0.45	0.55

Note 1: MSL 1 (moisture sensitivity level 1) classified according to IPC/JEDEC industry standard.

Note 2: Pocket position is relative to the sprocket hole measured as true position of the pocket, not the pocket hole.


DIE MARKINGS



Part Number	Laser Markings		
	Part # Marking Line 1	Lot_Date Code Marking Line 2	Lot_Date Code Marking Line 3
EPC2055	2055	YYYY	ZZZZ

DIE OUTLINE

Solder Bump View




DIM	Micrometers		
	MIN	Nominal	MAX
A	2470	2500	2530
B	1470	1500	1530
c		1175	
d		1350	
e		500	
f		250	
g		300	
h		825	
j		787.5	
k		225	

Pad 1 is Gate;


Pads 2, 4, 6 are Source;

Pads 3, 5 are Drain

Side View



RECOMMENDED LAND PATTERN
(units in μm)




Land pattern is solder mask defined
Solder mask opening is 180 μm
It is recommended to have on-Cu trace PCB vias

Pad 1 is Gate;
Pads 2, 4, 6
are Source;
Pads 3, 5 are Drain

DIM	Nominal
A	2500
B	1500
c1	1155
d1	1330
e	500
f1	230
g1	280
h1	805
j	787.5
k	225

RECOMMENDED STENCIL DRAWING
(units in μm)



DIM	Nominal
A	2500
B	1500
c1	1155
d1	1330
e	500
f1	230
g1	280
h1	805
j	787.5
k	225

Recommended stencil should be 4 mil (100 μm) thick, must be laser cut, openings per drawing.

The corner has a radius of R60.

Intended for use with SAC305 Type 3 solder, reference 88.5% metals content.

Split stencil design can be provided upon request, but EPC has tested this stencil design and not found any scooping issues.

Additional assembly resources available at <https://epc-co.com/epc/DesignSupport/AssemblyBasics.aspx>

Efficient Power Conversion Corporation (EPC) reserves the right to make changes without further notice to any products herein to improve reliability, function or design. EPC does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

eGaN® is a registered trademark of Efficient Power Conversion Corporation.
EPC Patent Listing: epc-co.com/epc/AboutEPC/Patents.aspx

Information subject to
change without notice.
Revised December, 2020